

XTeer IGO VG 100, 150, 220, 320

Description

XTeer IGO is an outstanding Industrial Gear Oil. It is formulated with excellent quality base oil technology and extreme pressure (EP) additives. It is especially designed to provide great protection against high loads, prevent damage on tooth- and friction surfaces. Furthermore, it shows excellent protection against rust and oxidation, while the excellent demulsification of the product allows easy water drain off.

Application

Recommended for Enclosed industrial gear drives operating under heavy loads, high peak loads or intermittent shock loads

- Enclosed spur, bevel, helical, herringbone and planetary gear drives
- AGMA EP gear
- Heavily loaded plain
- rolling-element bearings

Features / Benefits

- High load-carrying capacity for protection against scuffing and wear
- Excellent oxidation resistance and thermal stability
- Excellent deposit control for gearbox cleanliness
- Protects against rust and corrosion
- Fast water separation
- Quick foam release

Remarks

XTeer IGO meets or exceeds the requirements of

- US Steel 224
- ISO 12925-1 CKC/CKD
- GM LS 2 EP Gear Oil
- AGMA 9005-E02
- DIN 51517 Part 3

XTeer IGO VG	Density (15°C, kg/m ³)	Viscosity		Viscosity Index	Flash Point (°C)	Pour Point (°C)
		40°C	100°C			
100	875.7	93.2	11.1	104	222	-35
150	880.9	153	15.3	101	236	-25
220	886.6	221	19.4	99	240	-10
320	886.1	298	23.5	98	236	-17.5